

* Click the series number to check the product information

Control Button, Stick

FPC/FFC Connectors

Height: 0.85~5.32mm



- 0.5mm Pitch
- [6809](#) Ease of use, Robust, Front-lock
- [6811](#) Robust, Front-lock
- [6284](#) Non-ZIF
- [6806](#) Ease of use, Front-lock
- [6892](#) AOI-compatible, Front-lock
- [6244](#) Vertical, Non-ZIF

Battery

Board to Board Connectors

Stacking Height: 0.7mm



- 0.35mm Pitch
- [7129](#) Power 10A

Speaker, Mic., Sensor

FPC/FFC Connectors

Height: 0.85~1.75mm



- 0.3mm Pitch
- [6293](#) Lower-profile, Back-lock
- [6844](#) Space-saving, Front-lock
- 0.4mm Pitch
- [6824](#) Space-saving, Non-ZIF
- 0.5mm Pitch
- [6277](#) Low pin count, Back-lock
- [6298](#) Low pin count, Back-lock
- [6809](#) Ease of use, Robust, Front-lock
- [6811](#) Robust, Front-lock
- [6284](#) Non-ZIF
- [6806](#) Ease of use, Front-lock

Board to Board Connectors

Stacking Height: 0.6~2.0mm




- 0.35mm Pitch
- [7129](#) Power 10A
- [5861](#) Power 5A, Lower-profile
- [5843](#) Stacking height variations
- 0.4mm Pitch
- [5804](#) Stacking height variations

Main – Sub. PCB (I/O)

FPC/FFC Connectors

Height: 0.85~5.32mm



- 0.3mm Pitch
- [6293](#) Lower-profile, Back-lock
- [6844](#) Space-saving, Front-lock
- 0.4mm Pitch
- [6824](#) Space-saving, Non-ZIF
- 0.5mm Pitch
- [6809](#) Ease of use, Robust, Front-lock
- [6811](#) Robust, Front-lock
- [6284](#) Non-ZIF
- [6806](#) Ease of use, Front-lock
- [6892](#) AOI-compatible, Front-lock
- [6244](#) Vertical, Non-ZIF

Vibrator

Wire to Board Connectors

Height: 0.9~3.61mm



- [8041](#) 0.9mm Pitch
- [8040](#) 1.0mm Pitch
- [8005](#) 1.27mm Pitch