


\* Click the series number to check the product information

### Sub. PCB (Disk Drive)

#### FPC/FFC Connectors

Height: 0.85~2.2mm



- 0.2mm Pitch  
[6866](#) Space-saving, Front-lock
- 0.3mm Pitch  
[6293](#) Lower-profile, Back-lock  
[6844](#) Space-saving, Front-lock
- 0.4mm Pitch  
[6287](#) Ease of use, Front-lock
- 0.5mm Pitch  
[6809](#) Ease of use, Robust, Front-lock  
[6811](#) Robust, Front-lock  
[6284](#) Non-ZIF  
[6806](#) Ease of use, Front-lock  
[6892](#) AOI-compatible, Front-lock

### Shield Case

#### Shield Locks

Height: 1.8, 3.0mm




[8069](#) Better work efficiency

### Main – Sub. PCB (I/O)

#### FPC/FFC Connectors

Height: 0.85~5.32mm



- 0.2mm Pitch  
[6866](#) Space-saving, Front-lock
- 0.3mm Pitch  
[6293](#) Lower-profile, Back-lock  
[6844](#) Space-saving, Front-lock
- 0.4mm Pitch  
[6287](#) Ease of use, Front-lock
- 0.5mm Pitch  
[6809](#) Ease of use, Robust, Front-lock  
[6811](#) Robust, Front-lock  
[6284](#) Non-ZIF  
[6806](#) Ease of use, Front-lock  
[6892](#) AOI-compatible, Front-lock  
[6817](#) One-Action

